

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36; 30 & 31, T21-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 2 Page(s) 789)

(79.69 chs.)

Set post, witness cor. of secs. 25, 30, 31 and 36, from which

A Cedar 70" dia., bears S.36°E., 60 lks. dist.

A Fir 40" dia., bears N.20°W., 47 lks. dist.

A Maple 12" dia., bears S.81°W., 26 lks. dist.

A Maple 4" dia., bears N.40°E., 66 lks. dist.

(80.00 chs.) (South)

True cor. of secs. 25, 30, 31 and 36 in Pass Creek, 6 lks. wide, course SW.

A.R. Evans, Surveyor - Wit: Farrell - March 1949 - C.S. File 43/76

Set 1½" x 72" Galv. I.P. for wit. corner. Location determined from orig. BT, 70" Cedar S.36°E., 60 lks., down and dead.

Blazed and scribed new BTs:

14" Ash S.65°W., 66.0 ft. mkd. T21S R5W S36 CS BT.

15" Ash N.55°E., 70.0 ft. mkd. T21 R4 S30 CS BT.

No trees available in secs. 31 and 25.

B.H. McGillicuddy - July 1953 - C.S. File 41/182

This point falls in Pass Creek at a point 20.5 ft. South of the original witness corner of true corner. Witness corner set and represented by a 1½" Pipe.

New 10" Maple set, marked "CS S36 Tp 20 S, R5W" S.66°E., 65.2 ft. Map does say Tp 20 S)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Oct. 1964 - C.S. File 49/68-20

Found - 1½" Iron pipe on bank of Pass Creek.

Ash tree, N.55°E., 70.0 ft., scribing visible on open face, tree dead.

14" Maple S.66°E., 65.2 ft., shows scars. This tree across Pass Creek from corner.

Dead Ash tree, S.65°W., appears to be approx. correct dist. in thick blackberry jungle. Dist. not measured.

Reblaze and scribed:

14" Maple S.66°E., 65.2 ft. mkd. "T21S R4W W.C. S31 CS BT"

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36; 30 & 31, T21-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BT - 18" Alder, S.6°W., 65.8 ft. mkd. "T21S R5W WC S36 CS BT". Alder is across creek from corner, scribed 5 ft. high.
No other trees available.


BLM Resurvey by Wayne L. Rogers; Dale T. Bedell; Boyd W. Peterson; Garry L. Moore, Cadastral Surveyors and Garry L. Moore, Surveying Technician - Under Group #1406, Surveyed Feb. 2, 1988/Jan. 6, 1989 - (DCSO records Vol. 48 Page(s) 18606-07)

The true point for the cor. of secs. 25, 30, 31 and 36, determined at record bearing and distance from the original witness corner by McGillicuddy, in 1953, located in bank of Pass Creek where it is impracticable to establish a permanent monument.

From this point, the original witness cor. bears North, 0.310 chs. dist., perpetuated and recorded by Frear in 1938, from original evidence no longer in existence, further perpetuated and recorded by McGillicuddy in 1953, and further perpetuated and recorded by Godfrey in 1964; monumented with an iron pipe 1¼" dia., firmly set 3" below surface of ground, from which a bearing tree mkd. by McGillicuddy:

A Maple 25" dia., bears S.65°E., 87 lks. dist. with axe marks visible on partially healed blaze (tree appears to have slid toward creek.)
and a bearing tree mkd. by Godfrey:
An Alder 22" dia., bears S.3½°W., 96 lks. dist. with healed double blaze.

At the corner point
Set an alum. rod, 108" long, 3/4" dia., 96" in ground, with an alum. cap 3" dia. mkd:



1988

from which a new bearing object and reference monuments:

A brass tablet 3" dia., bears N.25½°E., 2.850 chs. dist., brass cap mkd. Oregon State Highway Dept. Bench Mark; brass cap is located 12 ft. from SE. end of bridge, in curb on S. side of bridge.

A stainless steel post, 29" long, 2½" dia., set 24" in the ground for a reference monument, bears N.40°E., 318.2 lks. dist., with brass cap mkd. RM T21S R4W S30 210 ft. to W Cor. 1988, and an arrow pointing to the corner.

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36; 30 & 31, T21-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A stainless steel post 28" long, 2½" dia., set 24" in the ground for a reference monument, bears N.50°W., 318.2 lks. dist., with brass cap mkd. RM T21S R5W S25 210 ft. to W. cor 1988, and an arrow pointing to the corner.

Fd. OK, Oct. 1993 by G. Riley - M 117-77

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20387-8)

At the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., determined at record bearing and dist. from the original witness cor.

Set a stainless steel post, 28", long, 2½" diam., 28" in the ground, with brass cap mkd.

T 21 S
R 5 W R 4 W
S 25 | S 30
S 36 | S 31
1998

No accessories taken.

Cor. is located N., 0.30 chs. dist. from the right bank of Pass Creek, 30 lks. wide, bank bears N.80°E. and S.80°W., course S.80°W.

NORTH 0.310 CHAINS

The original witness cor. to the cor. of secs. 25, 30, 31 and 36, monumented with an aluminum rod, 3/4" diam., firmly set, projecting 10 ins. above ground, with aluminum cap mkd. WC T21S R5W R4W S25 S30 S36 S31 1988 and an arrow pointing to the true point. This point now functions as Angle Point No. 1 and change the marks on the aluminum cap to now read

AP 1
T 21 S
R5W R4W
S 25 | S 30
1998

from which a bearing tree mkd. by McGillicuddy, in 1953, A maple, 24" diam., bears S.65°E., 87 lks., with partially healed blaze.

and reference monuments established by and a bearing object tied to by Rogers, Bedell, Peterson and Moore

continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T21-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A brass tablet, 3" diam., bears N.26°E., 285 lks. dist., with top mkd. OREGON STATE HIGHWAY DIV. BENCH MARK, brass tablet is located 12 ft. from the SE. end of the bridge, in the curb on the S. side of the bridge. (Record, N.25½°E.)

An iron post, 2½" diam., firmly set, projecting 7" above ground for a reference monument, bears N.40 3/4°E., 318.2 lks., with brass cap mkd. RM T21S R4W S30 210 FT T0 WC 1988 and an arrow pointing to the witness cor., the marks WC were changed to AP. (Record, N.40°E.)

An iron post, 2½" diam., firmly set flush with the ground for a reference monument, bears N.49¼°W., 318.2 lks. dist., with brass cap mkd. RM T21S R4W S26 210 FT T0 COR 1988 and an arrow pointing to the witness cor., the marks WC were changed to AP. (Record, N.50°W.)

Found OK by Les Roberts, April 2000 - M134-66