

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T21-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 788)

Set post cor. of secs. 19, 24, 25 and 30, from which
A Fir 8" dia., bears S.28°W., 24 lks. dist.
A Fir 6" dia., bears N.54°W., 183 lks. dist.
A Fir 4" dia., bears N.30°E., 65 lks. dist.
A Fir 7" dia., bears S.58°E., 131 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - March 10, 1958 - C.S. File 49/68-1

Found - Two orig. BTs now stumps only, good scribing visible. NE. and SW. BTs check bearing & dist. Also find 12" x 8" x 6" stone with chiseled + on top at corner. Cor. in N-S fence line, set by Banlau, Oct. 13, 1895
New BTs- 10" R.Fir bears S.79°E., 9.0 ft. scribed S30 T21S R4W CS BT.
22" R.Fir bears N.68°E., 27.0 ft. scribed S19 T21S R4W CS BT.
8" R.Fir bears N.85°W., 67.8 ft. scribed S24 T21S R5W CS BT.
12" R.Fir bears S.63°W., 32.4 ft. scribed S25 T21S R5W CS BT.

Fd. OK, Nov. 1964 by Godfrey - C.S. File 49/68-27
Fd. OK, Feb. 1981 by R. Kimberling - M 79-69
Fd. OK, July 1996 by L. Roberts - M 125-47

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20391-2)

The cor. of secs. 19, 24, 25 and 30, perpetuated by Byron, in 1958, monumented with a stone, 8x8x4", above ground, mkd X on top and OCT 13 1895 BY P ANLAUF on the side, from which the remains of an original bearing tree:
A decayed fir stump, size indeterminate, bears N.30°E., 65 lks., with scribe marks BT visible on opened blaze.
and the remains of bearing trees mkd. by Byron
A sawed fir stump, 38" diam., bears N.68°E., 41 lks., no marks visible.
A sawed fir stump, 13" diam., bears S.79°E., 13½ lks., with scribe marks CS visible on opened blaze.
continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A sawed fir stump, 15" diam., bears S.63°W., 49 lks., with healed blaze.

A sawed fir stump, 19" diam., bears N.85° W., 103 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28", long, 2½" diam., 28" in the ground, with brass cap mkd.

T 21 S
R 5 W R 4 W
S 24 | S 19
S 25 | S 30
1997

from which new bearing trees

A fir, 10" dia. bears N.27°E. 48 lks. mkd. T21S R4W S19 BT

A fir, 5" dia. bears S.80°W. 6 lks. mkd. T21S R5W S25 BT.

A fir, 6" dia. bears N.5¼°W. 29½ lks. mkd. T21S R5W S24 BT

No suitable accessory available in the SE quadrant.

Deposit a magnet in a white plastic case at the base of and reset stone alongside of stainless steel post.