

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T21-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 788)

-----  
Set ¼ sec. post, from which  
A Fir 4" dia., bears S.17°E., 79 lks. dist.  
A W.Oak 12" dia., bears S.56°W., 181 lks. dist.

W.F.Briggs - Nov. 1891 - For: Franz Analauf - Vol. 1 Page 192

-----  
Set post marked C.S., from which  
R.Fir 36" dia., bears S.80°E., 30 lks. dist.  
R.Fir 24" dia., bears N.34°W., 26 lks. dist.

Survey by Bruce A. Shaner - For: Lee Kruse & Weyerhaeuser Co.  
Feb. 1962 - RM 2-17

-----  
No valid evidence found except for very old fence line going due E. from computed corner. The fences going northerly & westerly are random. Valid bearing trees were non-existent.  
Set 1" x 36" steel pipe 1 ft. below top of field, from which  
6" D.Fir bears S.88°E., 31.8 ft. scribed ¼ S BT.  
9" D.Fir bears S.34°W., 65.3 ft. scribed ¼ S BT.  
The pipe is approx. 30 ft. West and 5 ft. North of corner of the field.

Fd. OK, July 1992 by Findorff - Land partition 1993-0016

Fd. OK, July 1996 by Les Roberts - M 125-47