

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T21-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 788)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.40°W., 49 lks. dist.
A Fir 8" dia., bears N.56°E., 89 lks. dist.

Douglas Co. Surveyor Office - Milo E. Godfrey - Nov. 5, 1964
-C.S. File 49/68-31

Fd 3/4" Pipe at approx. location. No BTs. No rec. of renewal

Survey by Charles W. Guile - For: Weyerhaeuser Co. - Nov. 17, 1986 - C.S. File 63/45(n) and M 103-9

Set 1" x 36" Iron pipe with cap stamped "Guile PLS 472"
Found - 3/4" Iron pipe bears S.75°20'46"W., 23.74 ft.
New BTs- 18" Fir bears N.53½°W., 8.8 ft. to "W" nail "E¼ S13 BT"
19" Fir bears N.86 3/4°E., 14.2 ft. to "W" nail "W ¼ S18 BT"

Fd. OK, Dec. 1991 by D. Peel - M 114-41

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20418)

From the ¼ sec. cor. of secs. 13 & 18, on the E. bdy of the Tp., reestablished by proportionate measurement by Guile, in 1986. There is no remaining evidence of the original corner, therefore, this position is accepted as the cor.; monumented with an iron pipe, 1½" diam., firmly set, projecting 9" above ground, with yellow plastic cap mkd. GUILÉ PLS 472, from which bearing trees mkd. by Guile

A fir, 21" dia. bears N.86 3/4°E., 22½ lks. with healed blaze.

A fir, 22" dia. bears N.53½°W., 15 lks. with healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, directly over the iron pipe, with brass cap mkd.

T 21 S
R5W R4W
¼
S 13 | S 18
1996

continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T21-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Deposit a magnet in a white plastic case at the base of the stainless steel post.

The cor. is located W., 0.90 chs., from County Road No. 116 (Territorial Highway), asphalt surfaced, 40 lks. wide, extends N.15°W. and S.15°E.

From this point, a point established by person(s) unknown, bears S.75°23'40"W., 0.360 chs., monumented with an iron pipe, 1¼" diam., firmly set, projecting 13", above ground, (alongside of which is an iron pipe, ¾" diam., firmly set, projecting 1" above ground)