

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T21-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 787)

Set post cor. of secs. 1, 6, 7 and 12, from which
A Fir 18" dia., bears N.84½°W., 135 lks. dist.
A Fir 20" dia., bears S.53°W., 198 lks. dist.
A Fir 24" dia., bears N.43°E. 425 lks. dist.
A Laurel 24" dia., bears S.83°E., 155 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Clete Putnam, crew - June 21, 1961 - C.S. File 49/68-8

Found - Orig. 18" now 44" Fir stump N.84½°W., 89.1 ft. We open and find good scribe marks.
Orig. NE. BT, down. SE. and SW. BTs, not found.
Set Brass cap at cor. mkd: County Surveyors Office

T 21 S
R5W

S 1	S 6
S 12	S 7

 R4W
1961

New BTs- 5" R.Fir N.58½°E., 54.0 ft. scribed S6 CS BT.
5" Chinquapin S.61°E., 26.6 ft. scribed S7 CS BT.
10" R.Fir S.43½°W., 42.4 ft. scribed S12 T21S R5W CS BT.
8" R.Fir N.40½°W., 53.1 ft. scribed S1 T21S R5W.

Fd. and used in BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #756, surveyed Aug. 1971/June 1972 (DCSO records Vol. 36 Page(s) 15017)

June 1990 - M 110-25 and M 110-29