

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 36, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 549)

A Hemlock 8" dia. for qr. sec. cor. marked ¼ S on West face, from which

A Fir 40" dia., bears S.71°W., 54 lks. dist. mkd. ¼ S BT.

A Fir 18" dia., bears S.30°E., 5 lks. dist. mkd. ¼ S BT.

Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

Found old BTs, very rotten.

Scribed:

40" Fir N.53°W., 28.4 ft.

6" Hemlock N.31°W., 16.8 ft.

Douglas Co. Surveyors Office - John M. Powell, and crew - April 1972 - C.S. File 56/12-8

Found - 40" D.Fir, down, N.53°E., (Rec. N.53°W.) 28.4 ft. scribe visible.

6" Hemlock now 10", N.31°W., 16.8 ft., shows good scar.

Haines T iron at ¼ corner.

New BT - 7" Hemlock S.54°E., 24.0 ft. scribed ¼ S31 CS BT.

BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Cadastral Surveyors - under Group #1392, surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18463)

The ¼ sec. cor. perpetuated and recorded by Haines in 1960, and further perpetuated and recorded by Powell in 1972, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 3" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE., from which the remains of an original bearing tree:

A rotted Fir stump 16" dia., bears S.30°E., 5 lks. dist., no marks remaining.

and bearing trees mkd. by Haines:

A rotted Fir stump size indeterminate, bears N.53°E., 38½ lks. dist., no marks remaining.

A Hemlock 18" dia., bears N.31°W., 25 lks. dist. with healed blaze.

and a bearing tree mkd. by Powell:

(Cont. Next Page)

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 36, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock 14" dia., bears S.54°E., 36 lks. dist., with scribe marks $\frac{1}{4}$ S31 CS visible on a partially healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron rod, with brass cap mkd:

T 21 S
R 7 W R 6 W
 $\frac{1}{4}$
S 36 | S 31
1987

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. OK Dec. 1991 by D. Baker - M 114-26

David Edwards - For: Seneca Jones Timber Co. - Nov 2012 - C.S. File 65/75-11

Found - 24" hemlock S.53°E., 23.6'
20" hemlock N.30W., 16.4'
Both with healed blaze
Steel fence post 2' south