

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 549-550)

-----  
Set post 5" dia., 4 ft. long, with marked stone 12" in ground for cor. to secs. 30, 31, 25 and 36, marked T21S S30 on NE.; R6W S31 on SE.; R7W S36 on SW.; S25 on NW. face, with one notch on S. and five on N. edge; from which

A Fir 20" dia., bears S.10°W., 28 lks. dist. mkd. T21S R7W S36 BT.

A Fir 20" dia., bears N.64°E., 39 lks. dist. mkd. T21S R6W S30 BT.

An Alder 8" dia., bears N.68°W., 39 lks. dist. mkd. T21S R7W S25 BT.

An Alder 6" dia., bears S.30°E., 130 lks. dist. mkd. T21S R6W S31 BT.

Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

-----  
Set 1" x 1" x 36" T. Iron, from which scribed  
36" Fir, N.72°W., 53.3 ft.  
30" Fir, N.40°W., 60.6 ft.  
6" Hemlock, S.82°E., 41.7 ft.

Douglas Co. Surveyors Office - John M. Powell, and crew - April 12, 1972 - C.S. File 56/12-7

-----  
Found - 36" D.Fir N.72°W., 53.3 ft., bark scribed.  
30" D.Fir N.40°W., 60.6 ft., bark scribed.  
6" Hemlock, S.82°E., 41.7 ft.  
Haines T. Iron at section corner.

New BTs- 10" D.Fir S.19°W., 12.5 ft., scribed T21S R7W S36 CS BT.  
5" D.Fir S.28°E., 37.2 ft., scribed S31 CS BT.

BLM Resurvey by Wayne L. Rogers and Dale T. Bedell, Cadastral Surveyors, under Group #1392, Surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18464)

-----  
The Sec. Cor., reestablished by proportionate measurement and recorded by Haines in 1960, and perpetuated and recorded by Powell in 1972, there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 6" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE., from which the remains of bearing trees mkd. by Haines:

(Cont. Next Page)

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T21-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Hemlock 18" dia., bears S.81°E., 63 lks. dist. with scribe mark 1 visible on partially healed blaze.

A Fir 41" dia., bears N.71°W., 80 lks. dist., with healed blaze.

A Fir stump 36" dia., bears N.39½°W., 90 lks. dist., no remaining marks.

and the remains of bearing trees mkd. by Powell:

A Fir 11" dia., bears S.28°E., 55 lks. dist. with healed blaze.

A rotted Fir stump 8" dia., bears S.20°W., 18 lks. dist., no remaining marks.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 20" in the ground, directly over the iron rod, with brass cap mkd:

T 21 S  
R 7 W R 6 W  
S 25 | S 30  
S 36 | S 31  
1987

from which new bearing trees

A Fir 11" dia., bears N.18°E., 26 lks. dist. mkd. T21S R6W S30 BT.

A Fir 10" dia., bears S.58°W., 27 lks. dist. mkd. T21S R7W S36 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. OK and used in BLM Resurvey by Dale T. Bedell, Group #1496, Surveyed July/Aug. 1989 - (DCSO records Vol. 50 Page(s) 18948)

Fd. OK Dec. 1991 by D. Baker - M 114-26  
Fd. BC & 4 BTs by Ron Rice - M158-79