

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25, T21-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 550)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for qr. sec. cor., marked $\frac{1}{4}$ S on West face; from which
A burnt Fir 50" dia., bears S.87°E., 77 lks. dist. mkd. $\frac{1}{4}$ S BT.
A burnt Fir 24" dia., bears N.87°W., 169 lks. dist. mkd. $\frac{1}{4}$ S BT.

Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

Set 1" x 1" x 36" T. Iron, from which scribed
10" Fir, N.08°W., 2.7 ft.
10" Fir, S.46°E., 2.1 ft.

BLM Resurvey by Wayne L. Rogers and Dale T. Bedell, Cadastral Surveyors, under Group #1392, surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18465)

The $\frac{1}{4}$ sec. cor., reestablished by proportionate measurement and recorded by Haines in 1960; there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 4" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE., from which the remains of bearing trees mkd. by Haines:

A Fir 13" dia., bears S.40°E., 3 $\frac{1}{2}$ lks. dist. with healed blaze.

A Fir snag, 10" dia., bears N.10°W., 4 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron rod, with brass cap mkd:

T 21 S
R 7 W R 6 W
 $\frac{1}{4}$
S 25 | S 30
1987

from which a new bearing tree

A Fir 19" dia., bears N.61°W., 24 lks. dist. mkd. $\frac{1}{4}$ S25 BT.