

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 129700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for sec. 31 only, T20-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 681)

Set post for ¼ sec. corner, from which
A V.Maple 7" dia., bears S.78°E, 37 lks.
A V.Maple 4" dia., bears S.62½°W., 11 lks.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

Location of corner established by proportional measurement.
Set an angle iron with brass cap at corner point, from which
60" Fir N.45°W., 87.6 ft.
54" Fir N.59°W., 101.5 ft.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22622-3

The ¼ sec. cor. of sec. 31 only, reestablished by Haines, Oregon PLS No. 239, in 1956, by proportionate measurement and is accepted as the cor., monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 5" above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines

A sawed, decayed fir stump, 47" dia., bears N.59½°W., 102.3 ft., with a healed blaze.

A sawed, decayed fir stump, 63" dia., bears N.44¾°W., 87.7 ft., with no marks visible.

and a bearing tree of unknown origin

A fir, 17" dia., bears N.86¼°E., 28.5 ft., with a healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T20S R6W

¼ S 31

T21S

2009

from which

A fir, 22" dia., bears N.43°W., 44.0 ft., mkd. T20S R6W S31 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.