

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 736)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
 Fir, 8" dia., bears N.7°W., 12 lks., mkd: ¼ S BT.
 Fir, 8" dia., bears S.14°W., 21 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2 & C.S. File 49/89-40

Looked for & not found.

Wilford N. Haines - For: Woolley Logging - 1962 - M27-31

No trace of Orig.
Set - 1"x1"x36" T iron from which:
 10" Hemlock N.68°E., 9.5 ft.
 8" Hemlock S.42°W., 4.5 ft.

BLM Dependent resurvey by Wayne Rogers & Dale Bedell, Cadastral Surveyor, under Group #1392, surveyed Aug./Nov. 1987 - (DCSO records Vol. 48 Page(s) 18471)

The ¼ sec. cor. of secs 30 & 31, reestablished by proportionate measurement & recorded by Haines in 1964; there is no remaining evidence of the orig. corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod 1" dia., firmly set, projecting 4" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE. from which the BTs mkd. by Haines:

 A Hemlock, 13" dia., bears S.62°E., 15 lks., with healed blaze.

 A Hemlock, 15" dia., bears N.45°W., 7 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 20" in the ground, directly over the iron rod, with brass cap marked:

 T 21 S R 6 W

 ¼ S 30
 S 31

 1987