

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 738)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which  
Maple, 4" dia., bears S.10°W., 31 lks., mkd: ¼ S BT.  
Fir, 30" dia., bears N.88°W., 32 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S.  
File 49/143-2 & C.S. File 49/89-40

-----  
Looked for & not found.

Wilford N. Haines - For: Woolley Logging - 1962 - M27-31

-----  
No trace of Orig.  
Set - 1"x1"x36" T iron  
6" Fir S.77°E., 29.5 ft.  
30" Fir N.54°W., 13.0 ft.

David Edwards - For: Seneca Jones Timber Co. - 12/2015 - C.S.  
File 65/92-1

-----  
Found - Haines' T-Iron  
A 46" dia., fir with bark scribes visible bears  
N.54°W., 13.0 ft.  
No sign of Haines' other BT  
New - A 13" dia., fir bears S.57°E., 22.4 ft., scribed "¼  
S30 BT", measured to center of tree at root crown  
A six ft steel post is set 2 ft N.89°E.