

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T20-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 680)

-
- Set post for cor. to secs. 5, 6, 31 and 32, from which
- A Fir 14" dia., bears S.65°E., 18 lks. dist.
 - A Hemlock 12" dia., bears N.2°E., 65 lks. dist.
 - A Maple 5" dia., bears S.2½°W., 25 lks. dist.
 - A Dogwood 6" dia., bears N.53°W., 40 lks. dist.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 744)

Found post much decayed and could not make bearing trees agree with the field notes given. Re-established this cor. by setting a post, 6" dia., 4 ft. long, 12" in ground, mkd. T20S S32 on NE.; T21S R6W S6 on SE.; R6W S31 on NW. face, with 5 notches on E. and 1 on W. edge; from which old trees:

- Hemlock 14" dia., bears N.2°E., 65 lks. dist. mkd. T20S R6W S32 BT.
- Fir 14" dia., bears S.65°E., 21 lks. dist. mkd. T21S R6W S5 BT.
- Maple 6" dia., bears S.2½°W., 25 lks. dist. mkd. T21S R6W S6 BT.
- Dogwood 6" dia., bears N.53°W., 40 lks. dist. mkd. T20S R6W S31 BT.

(This point 10.25 chs. West of cor. for 5 & 6 established by Wright)

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

Corner position located by proportional measurement. Set an angle iron with brass cap at point for corner, from which

- 52" Fir, N.32°W., 115.4 ft.
- 48" Fir, N.25°E., 151.3 ft.

Les Roberts - For: Seneca Jones Timber Co. - Nov. 1997 - M 127-70

Found-"T" iron set by Haines in survey M3-23

- 48" Fir Stump, N.25°E., 151.0' (scar vis.), 1956 BT.
- 52" Fir stump, N.32°W., 115.0' (scar vis.), 1956 BT.

Set - 6" Fir, N.26°E., 15.2', (scribed/washer/painted red)

- 8" Fir, N.57°W., 14.9', (scribed/washer/painted red)

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T20-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page(s) 22621

The cor. of secs. 31 & 32 only, reestablished by Haines, in 1956, by proportionate measurement, perpetuated by Roberts, in 1997, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 7" above the ground, from which the remains of BTs mkd. by Haines

A sawed, decayed fir stump, 39" dia., bears N.22³/₄°E., 150.8 ft., with no marks visible.

A sawed, decayed fir stump, 49" dia., bears N.35°W., 115.7 ft., with no marks visible.

and the remains of bearing trees mkd. by Roberts

A sawed fir stump, 7" dia., bears N.26¹/₄°E., 14.5 ft., with fragmentary scribe marks visible on a partially healed blaze.

A sawed fir stump, 10" dia., bears N.64³/₄°W., 16.0 ft., with fragmentary scribe marks visible on a partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2¹/₂" dia., 22" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T20S R6W

S 31 | S 32

S 6

T21S

2009

from which

A rebar, 30" long, 5/8" dia., driven 36" in the ground, buried 6" below the surface, for a reference monument, bears N.55°37'29"E., 10.66 ft., with aluminum cap mkd. RM T20S R6W S32 10.7 FT TO COR 2009 and an arrow pointing to the cor.

A fir, 17" dia., bears N.49¹/₂°W., 85.1 ft., mkd. T20S R6W S31 BT