

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 734-5)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 29, 30, 31, & 32, mkd. T 21 S S 29 on NE, R 6 W S 32 on SE, S 31 on SW, S 30 on NW face, with 5 notches on E & 1 on S edge; from which  
    Fir, 3" dia., bears N.23°E., 40 lks. mkd: T21S R6W S29 BT.  
    Fir, 40" dia. bears S.86°E., 30 lks. mkd: T21S R6W S32 BT.  
    Cedar, 10" dia. bears N.85°W. 42 lks. mkd: T21S R6W S30 BT  
    Fir, 10" dia. bears S.62°W., 7 lks. mkd: T21S R6W S31 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - Nov. 7, 1961 - C.S. File 49/143-9

-----  
Found - Haines "T" iron & cap at corner.  
    Cedar tree, now 16", N.85°W., 27 ft. This tree has been opened several years ago & faint scribing "21S2" visible on rotting face. No trace of any other BTs. found.

Do not set brass cap  
Reblaze & scribe 16" Cedar N.85°W., 27 ft. mkd: T21S R6W S30 CS BT.

New BTs- 11" Hemlock S.68°E. 27.6 ft. mkd: T21S R6W S32 CS BT  
    8" D.Fir N.65°E., 38.8 ft., mkd: T21S R6W S29 CS BT  
    44" D.Fir S.73°W., 33.5 ft., mkd: T21S R6W S31 CS BT

BLM remonumentation of certain orig. corner points by James E. Jelley, under group #350 surveyed April 1979 - (DCSO records Vol. 43 Page 16480-1)

-----  
The cor. of secs. 29, 30, 31, & 32, perpetuated & recorded by Haines in 1960, & further perpetuated & recorded by Godfrey in 1961, monumented with a T shaped iron rod, 1" cross section, firmly set, projecting 8" above ground, from which the remaining orig. BT:

    A Cedar, 18" dia., bears N.85°W., 42 lks., with fragmentary scribe marks visible on partially open orig. blaze & healed blaze by Godfrey.  
and BTs mkd. by Godfrey  
    A Fir, 10" dia., bears N.68°E., 58 lks. with healed blaze.  
    A Hemlock, 17" dia, bears S.68°E., 41. lks., with healed blaze.  
    A Fir, 46" dia, bears S.73°W., 51 lks., with healed blaze.

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>T 21 S R 6 W S 30   S 29 S 31   S 32 1979</p> <p>Reset T shaped iron rod alongside iron post.</p>						
<p>Fd. &amp; used on BLM Dependent resurvey by Wayne Rogers &amp; Dale Bedell, Cadastral Surveyor, under Group #1392, surveyed Aug./Nov. 1987 - (DCSO records Vol. 48 Page(s) 18470)</p>						
<p>BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19011)</p> <p>-----</p> <p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½" diam., firmly set, projecting 2" above ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"><tr><td>T21S</td><td>R6W</td></tr><tr><td>S30</td><td>S29</td></tr><tr><td>S31</td><td>S32</td></tr></table> <p style="text-align: center;">1979</p> <p>from which the remaining original bearing tree</p> <ul style="list-style-type: none"><li>A cedar, 18" dia., bears N.85°W., 42 lks., with three healed blazes.</li></ul> <p>and bearing trees mkd. by Godfrey, in 1961</p> <ul style="list-style-type: none"><li>A fir, 11" dia., bears N.68°E., 58 lks., with healed blaze.</li><li>A hemlock, 18" dia., bears S.68°E., 41 lks., with healed blaze.</li><li>A fir, 50" dia., bears S.74°W., 53 lks., with healed blaze.</li></ul>	T21S	R6W	S30	S29	S31	S32
T21S	R6W					
S30	S29					
S31	S32					
<p>FD. Ok by Carl Sweeden, 9/2008 - M156-68</p>						