TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 736)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 12" dia., bears N.47°W., 8 lks., mkd: ¼ S BT.
Fir, 8" dia., bears N.46°E., 17 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2 & C.S. File 49/89

Looked for & not found.

Wilford N. Haines - For: Woolley Logging - 1962 - M27-31

Reference point N.0°34'E., 207.6 ft. of point for 1/4 cor. - ¼ cor. not fd., not set
Set - 1"x1"x36" T iron for ref. point.
24" R.Cedar N.77½°E., 25.5 ft.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19011-2)

Point for the ¼ sec. cor. of secs. 29 & 30, determined at proportionate distance latitudinally between the cor. of secs. 29, 30, 31, & 32 & the cor. of secs. 19, 20, 29, & 30, and on line with a reference point established by Haines, in 1962, hereinafter described; there is no remaining evidence of the original corner.
Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd.

T21S R6W
¼
S30 | S29
1990

from which
A fir, 17" dia., bears S.82°E., 45 lks., mkd. ¼ S29 BT.
A hemlock, 14" dia., bears N.18°W., 8 lks., mkd. ¼ S30 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

N.0°15'30"W., bet. secs. 29 & 30 3.15 chains
A reference point established & recorded Haines in 1962, monumented with a "T" shaped iron rod, 1" dia., 24" below the ground surface. This point now becomes an angle point in the line.