

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 736-7)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 19, 20, 29, & 30, mkd. T 21 S S 20 on NE, R 6 W S 29 on SE, S 30 on SW, S 19 on NW face, with 5 notches on E & 2 on S edge; from which

Fir, 16" dia. bears N.38°E., 32 lks. mkd: T21S R6W S20 BT.
 Fir, 24" dia. bears S.69°E., 23 lks. mkd: T21S R6W S29 BT.
 Maple, 6" dia. bears S.41°W. 31 lks. mkd: T21S R6W S30 BT
 Fir, 16" dia. bears N.40°W., 32 lks. mkd: T21S R6W S19 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey & S. Bilow - May 20, 1958 - C.S. file 49/89-5

Found - 3 orig. BTs:

Orig. 24" now 48" down Fir shows good bark scribing "BT - - -" bears S.69°E., 15.2 ft.
 Orig. 16" now 24" Fir N.40°W., 21.1 ft. shows good scar, I do not open.
 Orig. 16" now 24" Fir snag N.38°E., 21.1 ft. shows good scar, I do not open.
 All BTs check for bearing & distance.

Set brass cap at cor. mkd: S19|S20 T21S R6W COUNTY SURVEYORS
S30|S29 OFFICE 1958

New BTs- 7" Cedar bears S.27°W., 31.5 ft., mkd: S30 T21S R6W CS BT
 8" Cedar bears S.19°E., 47.8 ft., mkd: S29 T21S R6W CS BT
 16" Maple bears N.80°E., 23.0 ft., mkd: S30 T21S R6W CS BT
 The orig. NW BT OK.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19012-3)

The cor. of secs. 19, 20, 29, & 30, perpetuated by Byron in 1958, monumented with an iron post, 1½" dia., firmly set, projecting 15" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T21S
S19 | S20
S30 | S29
 R6W
 1958

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

from which the remains of the original bearing trees
A fir snag, 24" diam., bears N.38°E., 32 lks., with illegible scribe marks on opened blaze.
A root hole, bears S.69°E., 23 lks., with a down fir alongside, 48" dia., with old bark blaze.
A fir, 38" dia., bears N.40°W., 32 lks., with healed blaze and bearing trees mkd. by Byron
A maple, 16" dia., bears N.80°E., 35 lks., with healed blaze.
A cedar, 19" dia., bears S.19°E., 72 lks., with healed double blaze.
A cedar, 15" dia., bears S.27°W., 48 lks., with healed blaze.
The corner is located on steep W. slope.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed May 2012 - DCSO records BLM Plat 2013-1, T21-6 and Vol. 58 Page(s) 22973-4

The cor. of secs. 19, 20, 29, & 30, monumented with an iron post, 1¼" dia., firmly set, projecting 20" above ground, with brass cap (properly) mkd.
from which the remains of the orig. BTs
A decayed fir stump, size indeterminate, bears N.38°E., 21.1 ft. with no marks visible.
A roothole bears S.60°E., 23.8 ft. with a fallen, decayed fir snag, 36" dia., lying alongside, with no marks visible. (Rec. S.69°E., 15.2 ft.)
A fir, 38" dia., bears N.40°W., 21.1 ft. with a healed blaze.
and the BTs mkd by Byron, 1958
A maple, 17" dia., bears N.80°E., 23.1 ft. with a healed blaze.
A cedar, 25" dia., bears S.15¾°E., 47.5 ft. with a healed blaze. (Rec. S.19°E.)
A cedar, 17" dia., bears S.27°W., 31.7 ft. with a healed blaze.
Latitude 43°43'18.00"N. Longitude 123°26'50.64"W.
(NAD 1983 (CORS 96))

Fd as per 2013 BLM by D.Edwards - 12/2015 - C.S. File 65/92-1