

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 738-9)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 17, 18, 19, & 20, mkd. T 21 S S 17 on NE, R 6 W S 20 on SE, S 19 on SW, S 18 on NW face, with 4 notches on E & 3 on S edge; from which

Fir, 14" dia. bears N.25°W., 30 lks. mkd: T21S R6W S18 BT.
Fir, 14" dia. bears N.21°E., 37 lks. mkd: T21S R6W S17 BT.
Maple, 12" dia. bears S.45°E. 13 lks. mkd: T21S R6W S20 BT
Fir, 3" dia. bears S.21°W., 83 lks. mkd: T21S R6W S19 BT.

Wilford N. Haines, #239 - For: Harold Woolley - Dec. 18, 1957
M 8-7 (and Haines field book, H-68)

Set Lot Marker from old BTs
Scribed: 28" Fir S.18°W., 44.0 ft.