

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 745)

-----

(10.56 chs. East of cor. for 31 & 32)  
 I set post 6" dia. in ground with marked stone 12", for closing cor. to secs. 5 and 6, marked T20S R6W S32 on NE.; T21S S5 CC on SE.; R6W S6 CC on SW. face, with 5 notches on E. and 1 on W. edges; from which  
 Alder 5" dia., bears N.31°E., 34 lks. dist. mkd. T20S R6W S32 BT.  
 Fir 40" dia., bears S.27°W., 27 lks. dist. mkd. T21S R6W S6 CC BT.  
 Fir 6" dia., bears S.33°E., 42 lks. dist. mkd. T21S R6W S5 CC BT.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

-----

Found SW. Fir BT.  
 Set an angle iron for corner.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22620-1

-----

The orig. closing cor. of secs. 5 and 6, T21S R6W bears South, 11.69 ft., perpetuated by Haines, in 1956, monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 2" above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree  
 A fir snag, 51" dia., bears S.27°W., 20.7 ft., with a healed blaze. (Record, 17.8 ft.)  
 and a bearing tree of unknown origin  
 A fir snag, 15" dia., bears S.10½°W., 20.3 ft., with scribe marks CC S6 BT visible on a partially healed double blaze.

At the corner point  
 Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T 20 S  
 S 32  
 -----  
 S 6 | S 5  
 C C  
 T21S R6W  
 2009

from which

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only (North)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A rebar, 30" long, 5/8" dia., driven 26" in the ground for a reference monument, bears S.45°52'27"E., 7.65 ft., with aluminum cap mkd. RM T21S R6W CC S5 7.7 FT TO COR 2009 and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 26" in the ground for a reference monument, bears S.34°19'53"W., 5.05 ft., with aluminum cap mkd. RM T21S R6W CC S6 5.1 FT TO COR 2009 and an arrow pointing to the cor.

Deposit a magnet in a white plastic case at the base of the stainless steel post.