

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 735)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which  
Fir, 36" dia., bears N.54°E., 12 lks., mkd: ¼ S BT.  
Fir, 36" dia., bears S.55°W., 57 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2

-----  
Looked for & not found.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19010)

-----  
Point for the ¼ sec. cor. of secs. 29 & 32, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T21S R6W  
¼ S29  
S32

1990

from which

A fir, 8" dia., bears N.89½°E., 16 lks., mkd. ¼ S29 BT.

A fir, 5" dia., bears S.31°E., 17½ lks., mkd. ¼ S32 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.