

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 737)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
 Fir, 36" dia., bears S.43°W., 35 lks., mkd: ¼ S BT.
 Fir, 36" dia., bears N.60°E., 25 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2

Looked for & not found.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19013)

Point for the ¼ sec. cor. of secs. 20 & 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd.

T21S R6W
¼ $\frac{S20}{S29}$
1990

from which

 A fir, 7" dia., bears S.22°E., 11 lks., mkd. ¼ S29 BT.

 A fir, 10" dia., bears N.13½°W., 15 lks., mkd. ¼ S20 BT.

At the corner point, found a "T" shaped iron rod, 30" long, 1" diam., projecting 1" above ground. I find no record of this monument.

Deposit a white "DEEP-1" magnetic marker at the base and the iron rod alongside the stainless steel post.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed May 2012 - DCSO records BLM Plat 2013-1, T21-6 and Vol. 58 Page(s) 22973-4

The ¼ sec, cor, of secs, 20 & 29 monument with a stainless steel post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd

from which the BTs mkd. by Bedell

 A fir, 13" dia., bears S.22°E., 7.3 ft., with a healed blaze.

 A fir, 13" dia., bears N.13½°W., 9.9 ft. with a healed blaze.