TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 739)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 48" dia., bears S.50°W., 47 lks., mkd: ¼ S BT.
Fir, 38" dia., bears N.45°W., 35 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey & S. Bilow - May 20, 1958 - C.S. file 49/89-4

Found - Both orig. BTs.
Orig. 38" now 48" snag shows good bark scribing "¼S" bears N.45°W., 23.1 ft.
Orig. 48" now 60" low cut stump bears S.50°W., 31.0 ft. Stump cut below any possible scribe marks.
Set brass cap at corner mkd: ¼ S17 T21S R6W COUNTY SURVEYORS
S20 OFFICE 1958
Note - I also find 6"x6"x6" stone at corner, not marked, may be corner stone.
New BTs- 6" R.Fir bears S.69°E., 23.7 ft. scribed ¼ S20 CS BT
14" Hemlock bears N.3°E., 37.0 ft. scribed ¼ S17 CS BT.