

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 741)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
 Fir, 6" dia., bears N.5°E., 13 lks., mkd: ¼ S BT.
 Fir, 6" dia., bears S.55°E., 12 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging Co. - Surveyed about 1955, map filed 5/1962 - C.S. File 51/234-1

Set T iron scribed 2 trees.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - May 8, 1962 - C.S. File 51/234-2

Found ¼ cor. as renewed by Wilford Haines.
 At corner fd. "T" iron & cap.
 32" D.Fir S.51°E., 21.3 ft. blazed & scribed.
 Scribing "¼" & "B" visible through pitch in still open scar. Haines metal disc fastened to this tree.
 20" D.Fir N.54°W., 18.8 ft. scribing "¼S BT" visible in open scar.
 No trace of orig. cor. fd.
 Corner lies in small, very steep draw running north.