

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 726)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 18" dia., bears N.47°W., 18 lks., mkd: ¼ S BT.
Laurel, 14" dia., bears N.35°E., 11 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2 & V.R. Tracy - April 1967 C.S. File 54/14

Looked for & not found.

Wilford Haines - For: Woolley Logging - Surveyed 1965, plated March 1967 - M32-71

Found - Orig. Fir BT & stump hole for Madrone BT.
Set - "T" iron & scribed:
24" Fir S.15°E., 51.0 ft.
20" Fir N.28°W., 54.0 ft.

Doug Co. Surveyors Office - V.R. Tracy - 4/3/1967 C.S. 54/14-33A

Fd. Haines' "T" iron & BTs mkd. by Haines - See M32-71 apparently set from same Fir & Laurel stump hole fd. by MEG & crew in 1961 at which time no scribe mks were found & we do not find any this visit. Chopped out Fir bears N.60°W., 11.9 ft. record N.47°W. - flat face - no scribe. Stump hole bears N.49°E., 7.3 ft. rec. N.35°E. - no remains left.
This note was added to the previous corner renewal system & signed by James Byron:
These corners searched for & orig. not fd. in 1961 by MEG, see C.S. File No. 49/143. V.R. Tracy returned to same corners in April 1967 not sufficient evidence, see C.S. File 54/14-33A. Added 3/15/2005 DCSO, JC.

Tony Hostetter - For Seneca Jones Timber - May 2008 - M155-71

Found - T post & both BTs (now stumps) described by Haines in 1965, from which
9" madrone, scribed "S33 ¼ BT" bears N.65°30'E., 6.3 ft. to spike.
11" Fir, scribed "S33 ¼ BT" bears S.85°52'E., 16.6 ft. to spike.
16" Fir scribed "S32 ¼ BT" bears S.13°30'W., 30.5 ft. to spike.
20" Fir scribed "32 ¼ BT" bears N.72°14'W., 15.9 ft.