

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19008)

Beginning at the cor. of secs. 28, 29, 32, & 33, perpetuated by Godfrey, in 1961, monumented with an iron post, 1½" diam., firmly set, projecting 12" above ground, with brass cap mkd.
COUNTY SURVEYORS OFFICE

T21S R6W
S29 | S28
S32 | S33
1961

from which the remains of the original bearing trees
A fir snag, 28" dia. bears S.31°E. 29 lks. w/scribe mark S visible on previously opened blaze. (Rec. 25 lks.)
A rotted fir stump, 15" dia., bears S.32°W., 19 lks., no marks remaining.
A sawed fir stump, 32" dia., bears N.31°W., 26½ lks., with axe marks visible. (Record, 23 lks.)
and a bearing tree mkd. by Godfrey
A fir, 23" dia., bears S.54½°W., 33½ lks., with healed blaze.
and a bearing tree mkd. by Tracy, in 1967
A fir, 22" dia., bears S.78°E., 30 lks., with healed blaze.
and new bearing trees
A fir, 8" dia., bears N.34¾°E., 206 lks., mkd. T21S R6W S28 BT.
A fir, 10" diam., bears N.88°W., 45½ lks., mkd. T21S R6W S29 BT.

From this point, the BLM Geodetic Control Station No. EC 41051, at latitude 43°42'25.640"N. & longitude 123°25'35.757"W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N.75°30'00"E., 1.320 chs., monumented with an aluminum cap, 3" diam., set flush with the ground, mkd. GPS EC 41051 1990 and a triangle.

Fd. BC & accessories by Tony Hostetter - May 2008 - M155-71
Fd. BC & BTs by Troy Rambo, Sept. 2012 - M164-19