TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 728)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 6" dia., bears N.75°E., 26 lks., mkd: ¼ S BT.
Fir, 40" dia., bears S.60°W., 27 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2 & C.S. File 49/89-40

Looked for & not found.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19009)

Point for the ¼ sec. cor. of secs. 28 & 29 at proportionate distance; there is no remaining evidence of the orig. corner. Set a stainless steel post, 28" long, 2½" diam., 20" in the ground, with brass cap mkd. T21S R6W

¼
S29 | S28
1990

from which
A fir, 6" dia., bears N.30°E., 85 lks., mkd. ¼ S28 BT.
A fir, 10" dia., bears N.8°W., 54 lks., mkd. ¼ S29 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Troy Rambo - For: Seneca Jones Timber Co. - 9/2012 - M164-19

Found - Brass cap & record BTs
Bark Scribed: "¼ S28 BT" on a 14" Alder, bears N.54°E., 12.4 ft.
"¼ S28 BT" on a 13" Alder, bears S.79°W., 17.6 ft.