

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 728)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 20, 21, 28, & 29, mkd. T 21 S S 21 on NE, R 6 W S 28 on SE, S 29 on SW, S 20 on NW face, with 4 notches on E & 2 on S edge; from which
Fir, 24" dia. bears N.66°E., 45 lks. mkd: T21S R6W S21 BT.
Fir, 14" dia. bears S.36°E., 21 lks. mkd: T21S R6W S28 BT.
Fir, 14" dia. bears S.47°W., 25 lks. mkd: T21S R6W S29 BT.
Fir, 18" dia. bears N.85°W., 20 lks. mkd: T21S R6W S20 BT.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - Oct./Nov. 1961 - C.S. File 49/143-8

Found - Badly burned Fir snag, N.66°E., 29.7 ft. Did not open.
Fir snag, now 24", S.36°E., 13.9 ft., opened & fd. good reverse scribing "8"
Fir snag, now 27", S.47°W., 16.5 ft. shows good scar did not open.
Fir stump, now 36", N.85°W., 13.2 ft. shows scar, did not open.
Set - Brass cap mkd: COUNTY SURVEYORS T21S R6W S20|S21
OFFICE, 1961 S29|S28
New BTs- 51" D.Fir S.68°W., 50.0 ft., mkd: T21S R6W S29 CS BT
8" D.Fir S.71°E., 54.4 ft., mkd: T21S R6W S28 CS BT
11" Chinquapin N.51°E., 48.5 ft., mkd: T21S R6W S21 CS BT
7" D.Fir North 51.2 ft. mkd: T21S R6W S20 CS BT

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1541, surveyed May/July 1990 - (DCSO records Vol. 50 Page(s) 19009-10)

The cor. of secs. 20, 21, 28, & 29, perpetuated by Godfrey, in 1961, monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T21S
S20 | S21
S29 | S28
R6W
1961

from which the remains of the original bearing trees
A burnt fir snag, 30" dia., bears N.66°E., 45 lks., with burnt blaze.
continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A fir stump, 20" dia., bears S.36°E., 21 lks., with scribe mark B visible on opened blaze.
A rotted fir stump, 28" dia., bears S.47°W., 26 lks., no marks remaining. (Record, 25 lks.)
A rotted fir stump, 36" dia., bears N.80°W., 20 lks., with axe marks on rotted blaze. (Record, N.85°W.)
and the remains of bearing trees mkd. by Godfrey
A fir, 17" dia., bears N.52°E., 73 lks. with healed blaze.
A fir snag, 10" dia., bears S.70¾°E., 82 lks. with healed blaze.
A fir, 19" dia., bears N.1¾°W., 77 lks. with healed blaze.
and new bearing trees
A Fir, 18" dia., bears S.48½°E., 62 lks., mkd. T21S R6W S28 BT.
A fir, 8" dia., bears S.73½°W., 40 lks., mkd. T21S R6W S29 BT.

Troy Rambo - For: Seneca Jones Timber Co. - 9/2012 - M164-19

Found - Brass cap & record BTs
Found - A new 17" D.Fir with scribed - bears S.31°W., 24.1 ft.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed May 2012 - DCSO records BLM Plat 2013-1, T21-6 and Vol. 58 Page(s) 22973-4

The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 1¼" dia., firmly set, projecting 9" above ground with brass cap (properly) mkd.
from which the remains of the original bearing trees
A broken, decayed fir stump, size indeterminate, bears N.66°E., 29.7 ft. with no marks visible.
A hollowed, decayed fir stump, 20" dia., bears S.36°E., 13.9 ft. with no marks visible.
A decayed fir stump, 28" dia., bears S.47°W., 17.2 ft. with no marks visible.
A decayed fir stump, 30" dia., bears N.80°W., 13.2 ft. with no marks visible.
and the remains of BTS mkd by Godfrey, 1061
A fir, 23" dia., bears N.1°E., 50.8 ft. with a healed blaze. (Rec. N.1¾°W.)
A chinquapin, 19" dia., bears N.52°E., 48.2 ft. with a healed blaze.
A decayed fir snag, 13" dia., bears S.68½°E., 57.2 ft. with no marks visible. (Rec. S.70¾°E., 54.1 ft.)

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the BTs mkd. by Bedell

A fir, 29" dia., bears S.48½°E., 40.9 ft. with a healed blaze BT.

A fir, 14" dia., bears S.73½°W., 26.4 ft., with a healed blaze BT.

and a new BT

A fir, 16" dia., bears S.30¾°W., 24.1 ft., mkd: T21S R6W S29 BT.

Latitude 43°43'16.59"N Longitude 123°25'40.37"W
(NAD 1983 (CORS 96))