

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 731)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 16, 17, 8, & 9, mkd. T 21 S S 9 on NE, R 6 W S 16 on SE, S 17 on SW, S 8 on NW face, with 4 notches on E & S edges; from which

Alder, 5" dia. bears N.22°E., 44 lks. mkd: T21S R6W S9 BT.

Dogwood, 3" dia., bears S.20°E., 17 lks., mkd: T21S R6W S16 BT.

Alder, 4" dia. bears S.21°W., 18 lks. mkd: T21S R6W S17 BT

Fir, 8" dia., bears N.30°W., 57 lks., mkd: T21S R6W S8 BT.

Wilford N. Haines - For: Woolley Logging Co. - Surveyed about 1955, map filed 5/1962 - C.S. File 51/234-1

Found - NW BT & set "T" iron.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - April 1962 - C.S. File 49/143-26

Found - Haines "T" iron at corner & 36" Fir N.30°W., 37.6 ft. chopped open & found good scribing, part of "R" or "B".

No trace of any of the other 3 orig. BTs.

Blaze & rescribe 36" Fir N.30°W., 37.6 ft. mkd: T21S R6W S8 CS BT.

New BTs- 9" Hemlock N.52°E., 52.9 ft. mkd: T21S R6W S9 CS BT

10" Hemlock S.58°E. 31.8 ft. mkd: T21S R6W S16 CS BT

9" Hemlock S.14°W., 35.7 ft. mkd: T21S R6W S17 CS BT

DO NOT SET BRASS CAP

Corner lies in slide area on a very steep NW slope approx. 100 ft. south of a sharp draw running NE.