

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 333700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only, T20-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 680)

Set post for ¼ sec. corner, from which
A Fir 10" dia., bears S.59°E., 40 lks.
A Wh. Willow 4" dia., bears S.62½°W., 12 lks.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

Location of corner determined by proportional measurement.
Set an angle iron with brass cap at corner point, from which
16" Fir, N.55°E., 45.2 ft.
16" Fir, N.04°E., 25.2 ft.

Fd. OK April 1987 by D. Marx - M 105-45
Fd. OK Oct. 1994 - M 121-24 A&B

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page(s) 22617

The ¼ sec. cor. of sec. 33 only, reestablished by Haines, in 1956, by proportionate measurement and is accepted as the cor. monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 6" above the ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE laying alongside, from which bearing trees mkd. by Haines

A fir, 40" dia. bears N.3½°E., 25.0 ft with a healed blaze

A fir, 35" dia. bears N.53¾°E. 45.0 ft with a healed blaze

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T20S R6W

¼ S 33

T 21 S

2009

Deposit a magnet in a white plastic case at the base of the stainless steel post.