

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 727)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 24" dia., bears S.6°W., 26 lks., mkd: ¼ S BT.
Fir, 24" dia., bears N.5°E., 5 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2

Looked for & not found.

Wilford Haines - For: Woolley Logging - Surveyed 1965, plated March 1967 - M32-71

Corner set by single proportional measurement.
Set - "T" iron & scribed:
10" Madrone N.69°W., 23.0 ft.
40" Fir S.86°W., 13.6 ft.

Douglas Co. Surveyors Office - V.R. Tracy - April 4, 1967 C.S. File 54/14

Statement in the corner renewal book -
"Note - These corners searched for & orig. not found in 1961 by M.E.G., see C.S. file No. 49/143. V.R. Tracy returned to same corners in April 1967, not sufficient evidence, see C.S. File No. 54/14 Signed James W. Byron"

I can not find any corner report to support this statement in C.S. File 54/14. 7/31/2002 - DCSO JC

Ronald L Rice - March 2015 - March 2015 - C.S. File 65/87-38

Found - "T" Iron per County Survey File M32-71. Firmly set extending 24" above ground.
(Rec 10" Madrone N.69°W 23.0')—stump sprout no marks
40" D.Fir snag bears S.86°W., 13.6' - healed face
New - 10" D.Fir bears N.74°W., 12.9 ft. - blazed, scribed ¼ S28 BT
13" D.Fir bears S.22°W 15.4 ft. - blazed scribed ¼ S33 BT
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
Compass Declination 16° East