

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

Location of corner established by proportional measurement.
 Set an angle iron with brass cap at corner point, from which
 8" Fir, N.55°W., 17.1 ft.
 14" Fir, N.75°E., 13.8 ft.

Fd. OK, April 1987 by D. Marx - M 105-45

Fd. OK, Oct. 1994 - M 121-24 A&B - Mon. is S.0°11'59"E., 1.54' from the true intersection point.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22616-7

The ¼ sec. cor. of sec. 4 only, T21S R6W, established by Haines, in 1956, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 4" above the ground (alongside of which is a galvanized steel pipe, 3/4" dia., firmly set, projecting 18" above the ground, of unknown origin), with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE, from which bearing trees mkd. by Haines

A fir, 39" dia., bears N.78°E., 13.9 ft., with a healed blaze.

A fir, 35" dia., bears N.57°W., 17.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the "T" shaped iron rod and the galvanized steel pipe, with brass cap mkd.

T 20 S
 ¼ S 4
 T 21 S R 6 W
 2009

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ronald L. Rice, Ward NW - Seneca Jones Timber Co. - May 2010 - M 160-58

Found - ¾" BLM brass cap dated 2009* with the following accessories:

38" D.Fir bears N.77°E., 13.9' - healed face.

32" D.Fir bears N.57°W., 16.7' - healed face.