

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 719)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which Fir, 18" dia., bears N.33°W., 45 lks., mkd: ¼ S BT.
Dogwood, 3" dia., bears S.72°E., 8 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - 1961 - C.S. File 49/143-2 & C.S. File 49/89-40

Looked for & not found.

Wilford Haines - For: Woolley Logging - Surveyed 1965, plated March 1967 - M32-71

Found - 18" now 26" Fir N.33°W., 45 lks.
Set - "T" iron & scribed:
18" Fir N.67°E., 38.0 ft.
20" Fir S.40°W., 37.5 ft.

Douglas Co. Surveyors Office - V.R. Tracy - April 4, 1967 - C.S. File 54/14-33

Found Haines' "T" iron & BTs as recorded on M32-71 for ¼ S28|S27 - 26" fir N.33°W., 29.7 ft. face & slope measurement does not show & axe scar or do we find bark scribe - There is & axe mk. 3 ft. above ground only.
(Note - This report is typed exactly as it was written)

This note was added to the previous corner renewal system & signed by James Byron:
These corner(s) searched for & orig. not fd. in 1961 by MEG, see C.S. File No. 49/143.
V.R. Tracy returned to same corner(s) in April 1967 not sufficient evidence, see C.S. File 54/14(-33).
Added 3/15/2005 DCSO, JC.

Ronald L Rice - For: Seneca Jones Timber Co. - 3/2015 - M169-17

Found - T Iron per M32-71 with the following accessories:
30" D.Fir stump bears N.33°W., 29.7' - no marks
26" D.Fir bears N.67°E., 38.0' - healed face
33" D.Fir stump bears S.40°W., 37.5' - healed face
New BT - 7" D.Fir bears S.4°W., 17.8', - blazed, scribed ¼ S28 BT
Steel post adjacent to corner