

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 720)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 21, 22, 27, & 28, mkd. T 21 S S 22 on NE, R 6 W S 27 on SE, S 28 on SW, S 21 on NW face, with 3 notches on E & 2 on S edge; from which
 Fir, 48" dia. bears N.20°E., 20 lks. mkd: T21S R6W S22 BT.
 Fir, 8" dia., bears S.49°E., 15 lks. mkd: T21S R6W S27 BT.
 Fir, 10" dia. bears S.33°W., 52 lks. mkd: T21S R6W S28 BT.
 Fir, 12" dia. bears N.42°W., 42 lks. mkd: T21S R6W S21 BT.

Wilford N. Haines - For: Woolley Logging - 11/1960 - M20-77

Set - 1"x1"x36" T. iron from Orig. BTs
 12" Fir S.34°E., 36.8 ft.
Note - F.B. H-74 says S.34°W., DCSO, VL 9/1990

Ronald L Rice - For: Seneca Jones Timber Co. - Mar 2015 - M169-17

Found - T Iron per M20-77 with the following accessories:
 55" D.Fir bears N.26°E., (Record N.20°E., 13.2')
 16.0' - bark scribed
 16" D.Fir staub bears S.49°E., (Record 9.9') 10.7'
 - no marks
 21" D.Fir bears S.33°W., (Record 34.3') 36.8' - bark scribed
 27" D.Fir bears N.42°W., (Record 27.7') 28.2' - healed face.
 18" D.Fir stump bears S.34°E., 36.8'- no marks
 Steel post adjacent to corner