

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 721)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 15, 16, 21, & 22, mkd. T 21 S S 15 on NE, R 6 W S 22 on SE, S 21 on SW, S 16 on NW face, with 3 notches on E & S edge; from which

- Fir, 24" dia. bears N.73°E., 30 lks. mkd: T21S R6W S15 BT.
- Fir, 24" dia. bears S.81°E., 24 lks. mkd: T21S R6W S22 BT.
- Fir, 12" dia. bears S.36°W., 12 lks. mkd: T21S R6W S21 BT.
- Fir, 30" dia., bears N.6°W., 56 lks. mkd: T21S R6W S16 BT.

-----  
Wilford N. Haines - For: Woolley Logging - 11/1960 - M20-77

- Found - Scribe on slab of old BT  
Set - 1"x1"x36" T. iron & scribed  
10" Fir N.80°E., 19.0 ft.  
6" Fir S.47°E., 5.5 ft.  
6" Fir N.69°W., 4.7 ft.  
9" Fir S.24°W., 24.5 ft.

-----  
David Edwards - For: Seneca Jones Timber Co. - Jan. 2000 - CS File 65/29-1

- Found - 1"x1" T-iron (1960)  
19" Fir N.80°E., 19.0 ft.  
10" Fir S.47°E., 5.5 ft.  
22" Fir S.24°W., 24.5 ft.  
New BT - 24" Fir N.15°W., 27.15 ft. to nail set side center below stump height, scribed S16 BT.