TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 722)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 48" dia., bears S.47°E., 30 lks., mkd: ¼ S BT.
Fir, 40" dia., bears N.45°W., 68 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey - Sept. 1962 - C.S. File 49/143-31

Found - Fir, now 70", S.47°E., 19.8 ft. to face. Chop open & find good scribing "S BT"
Stump of Fir snag, 60" N.45°W., 44.9 ft. to face. Good bark scribing, "¼S" on loose piece of bark lying at base of snag.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962
T21S R6W ¼ S16|S15

New BTs- 7" D.Fir N.28°E., 13.8 ft. mkd: ¼ S15 CS BT
10" D.Fir N.17°W., 11.4 ft. mkd: ¼ S16 CS BT