

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 724)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which Cedar, 14" dia., bears N.44°W., 55 lks., mkd: ¼ S BT.  
\*Fir, 8" dia., bears N.69°E., 48 lks., mkd: ¼ S BT.  
(Note - in our typed copy of the notes, on the 2<sup>nd</sup> BT, Fir was lined out and Cedar & W.N.H #239 was written beside it.)

Wilford N. Haines - For: Woolley Logging Co. - Dec. 1961 - C.S. File 51/222-1

-----  
Found - 14" Cedar N.44°W., 55 lks.  
8" Cedar N.69°E., 48 lks.  
Set - 1"x1"x36" T iron.  
5" Fir N.70°E., 73.0 ft.

Harvey Christensen - For: Seneca Jones Timber Co. 1/1999 - M131-17

-----  
The ¼ corner common to secs. 9 & 10 was set at proportionate distance after an extensive search failed to recover the orig. corner BTS set in the 1884 GLO survey  
Set - 5/8"x30" rebar w/YPC "NTCI LS 2603" 0.2 ft above ground.  
16" D.Fir N.20°E. 17.8 ft. blazed & scribed: "¼ S10 BT"  
12" BLM Maple, N.43°W., 4.6 ft., blazed & scribed: "¼ S9 BT"  
9" D.Fir S.20°W., 25.0 ft. blazed & scribed: "¼ S9 BT"  
5" D.Fir, S.30°E., 23.7 ft., blazed & scribed: "X BT"  
6 ft. steel post 2 ft. South.  
Fd. possible orig. Cedar (snag) West about 30 ft. - badly burnt.