

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor Secs 3, 4, 9, & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 724)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 3, 4, 9, & 10, mkd. T 21 S S 3 on NE, R 6 W S 10 on SE, S 9 on SW, S 4 on NW face, with 5 notches on S & 3 on E edge; from which

Fir, 5" dia., bears N.10°E., 51 lks., mkd: T21S R6W S3 BT.

Willow, 3" dia. bears S.19°E. 12 lks. mkd: T21S R6W S10 BT

Oak, 3" dia., bears S.51°W., 9 lks., mkd: T21S R6W S9 BT.

Balm, 3" dia. bears N.17°W., 49 lks. mkd: T21S R6W S4 BT.

-----  
Wilford N. Haines - For: Woolley Logging Co. - Dec. 1961 - C.S. File 51/222-1

-----  
Found - 5" Fir N.10°E., 51 lks., now 36"

Set - 1"x1"x36" T iron.

18" Fir S.40°W., 47.5 ft.

30" Fir N.2°W., 39.2 ft.

-----  
BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyors, under Group #1231, surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18060)

-----  
The cor. of secs. 3, 4, 9, & 10, perpetuated & recorded by Haines in 1961, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 14" above ground, with washer mkd:

WILFORD N HAINES

239

SURVEY POINT

DRAIN OR

from which the remains of an orig. BT

A fir snag, 50" dia., bears N.10°E., 51 lks., with fragmentary scribe marks visible on opened blaze.

and BTS mkd. by Haines

A Fir, 38" dia., bears S.39°W., 68 lks., with healed blaze & scribe marks 363 visible on bark blaze.

A Fir, 30" dia., N.3°W., 89 lks., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, directly over iron rod, with brass cap marked:

T21S R6W

S 4 | S 3

S 9 | S 10

1985

continued next page

TOWNSHIP 21 RANGE 6 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor Secs 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new BTs  
A fir, 6" dia. bears N.9½°E., 43 lks. mkd: T21S R6W S3 BT.  
A fir, 16" dia. bears S.23°E. 42 lks. mkd: T21S R6W S10 BT  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.  
From this point, USGS triangulation station "SOUTH FORK" bears S.27°40'E., 83.16 chs., monumented with a standard brass tablet, 3½" dia., cemented in a boulder, flush with ground, with top mkd. SOUTH FORK 1940

---

Fd. Ok 10/1994 - M121-24 A&B

---

Harvey Christensen - For: Seneca Jones Timber Co. - 1/1999 - M131-17

-----

FOUND - 1985 BLM 3.0" BC 0.3 ft. above ground  
BTs - 42" D.Fir, S.39°W., 44.9 ft., scribing visible  
14" D.Fir, N.09°E., 28.4 ft., scribing visible  
13" R.Alder, S.15°E., 5.4 ft., scribing visible  
25" D.Fir, S.23°E., 27.7 ft. (Record), blown down  
35" D.Fir, N.5°W., 38.9 ft., scribing visible  
Set - 6 ft, steel post 1 ft. North

---

Ronald L. Rice, Ward NW - Seneca Jones Timber Co. - May 2010 - M 160-58

-----

Found - ¾" BLM brass cap dated 1985 with the following accessories:  
48" D.Fir bears S.39°02'W., 45.7' - Healed face  
37" D.Fir bears N.3°01'W., 58.2' - healed face  
20" D.Fir bears N.9°11'E., 28.1' - Healed face  
18" rotted D.Fir stub bears N.8°14'E., 33.5' - axe work visible  
13" Alder snag bears S.15°E., 5.4' - healed face

---

2