

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 725)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 4" dia., bears S.80°W., 5 lks., mkd: ¼ S BT.
Fir, 6" dia., bears S.78°E., 10 lks., mkd: ¼ S BT.

Wilford N. Haines - June 1959- C.S. File 51/27-3

Found - Rock with X and both old BTs dead.
Set - 1"x1"x36" T iron attached cap 1 1/16" dia.,
inscribed "Survey Point - Wilford N. Haines #239,
Drain Oregon"
48" Fir S.53°E., 50.9 ft.
26" Fir N.49°22'E., 185.3 ft.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyors, under Group #1231, surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18061)

The 1/4 sec. cor. of secs. 3 & 4, perpetuated & recorded by Haines in 1958, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 10" above ground, with washer mkd:

WILFORD N HAINES
239
SURVEY POINT
DRAIN OR

from which the remains of the orig. BTs

A decayed fir stump, size indeterminate, bears S.78°E., 10 lks., no marks visible.

A sawed fir stump, 26" dia., bears S.80°W., 5 lks., with fragmentary scribe marks visible on opened blaze.
and the remains of BTs mkd. by Haines

A fir snag, 51" dia., bears N.49°E., 275 lks., with healed blaze.

A fir snag, 53" dia., bears S.55°E., 74 lks., with scribe marks ¼ S3 BT visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with brass cap marked:

T21S R6W
¼
S 4 | S 3
1984

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new BTs
A fir, 4" dia., bears N.52°E., 7½ lks., mkd: X BT.
A fir, 10" dia., bears N.0½°W., 14 lks., mkd: ¼ S4 BT.

Fd. Ok 10/1994 - M121-24 A&B

Ronald L. Rice, Ward NW - Seneca Jones Timber Co. - May 2010
- M 160-58

Found - 3¼" BLM brass cap dated 1984 with the following accessories:
45" D.Fir snag bears S.53°07'E. 51.3', bark scribing visible.
18" D.Fir bears N.2°28'W., 9.1' - healed face.
New BT - 16" D.Fir bears S.63°E., 13.5' - blazed, scribed "¼" S3 BT"