

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 719)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on N face; from which Laurel, 20" dia., bears S.12°E., 13 lks., mkd: ¼ S BT. Oak, 14" dia., bears N.60°E., 21 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - 1961 - C.S. File 49/143-2 & 49/89-40

-----  
Looked for not found.

BLM Dependent resurvey by Wayne Rogers & Dale Bedell, Cadastral Surveyors, under Group #1392, surveyed Aug./Nov. 1987 - (DCSO records Vol. 48 Page(s) 18468-9)

-----  
Point for ¼ sec. cor. of secs. 27 & 34, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T21S R6W  
¼  $\frac{S\ 27}{S\ 34}$   
1987

from which

A fir, 11" dia., bears S.17¼°E., 40 lks., mkd: ¼ S34 BT.

A fir, 9" dia., bears N.56°W., 23 lks., mkd: ¼ S27 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. Ok 2/1994 - M118-39