

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 720)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
 Fir, 16" dia., bears S.45°E., 23 lks., mkd: ¼ S BT.
 Fir, 10" dia., bears N.45°W., 19 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging - 11/1960 - M20-77

Found - Both Orig. BTs
Set - 1"x1"x36" T. iron

BLM remonumentation of certain orig. corner points by James E. Jelley, under group #350 surveyed April 1979 - (DCSO records Vol. 43 Page 16480)

The ¼ sec. cor. of secs. 22 & 27, perpetuated & recorded by Haines, in 1960, monumented with a T shaped iron rod, 1" cross section, firmly set, projecting 8" above ground, from which the remains of the orig. BTs:

 A sawed fir stump, 16" dia., bears N.50½°W., 19 lks., with healed orig. blaze & scribe marks ¼ S22 BT visible by Haines on bark blaze. (Rec. N.45°W.)

 A fir, 34" dia., bears S.50½°E., 23 lks., with healed orig. blaze & scribe marks ¼ S27 BT visible by Haines on bark blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

 T21S R6W
 ¼ $\frac{S\ 22}{S\ 27}$
 1979

from which a new BT

 A fir, 10" dia., bears N.4°W., 140 lks., mkd: ¼ S22 BT.
 reset T shaped iron rod alongside iron post.

Douglas Co. Surveyors Office - Stephen J. Flause - Terrie Franssen - April 15-16, 1992 - C.S. File 64/26-2

Found - "T" iron with brass washer mkd. RLS 239 protruding 10" above ground. (1960)
 ¾" brass cap on 2½" dia., iron post, firmly set protruding 2" above ground. Cap marked US Bureau of Land Management Dept. of Interior 1979 (next to "T" iron)

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

16" Fir now a 36" DHB D.Fir with a fully healed double blaze (orig. tree) rescribed with the bark scribing "¼ S27 BT", 1960, bears S.50½°E., 16.4 ft. (Orig. rec. S.50½°E., 15.2 ft.)
10" Fir now a 3½' tall 16" dia., D.Fir stump with a fully healed double blaze, with the bark scribing "¼ S22 BT" bears N.50½°W., 12.5 ft. (orig. BT rescribed by Haines, 1960)
10" Fir now a 17" D.B.H. D.Fir with a fully healed double blaze bears N.4°W. 92.4 ft. (1979 BLM tree)
New BT - 5" D.B.H. D.Fir scribed "¼ S27 CS BT" on a double blaze bears S.74°W., 35.8 ft.
Note - Corner is on West slope just off crest of north-south ridge where ridge intersects east-west cutting line; small trees to north & old growth to south of line.