

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 722)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which Hemlock, 20" dia., bears S.60°W., 36 lks., mkd: ¼ S BT. Fir, 36" dia., bears N.7°E., 20 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging - 11/1960 - M20-77

Found - No trace of orig. corner.
Set - 1"x1"x36" T. iron & scribed
6" Hemlock N.73°W., 14.0 ft.
12" Alder S.13°E., 10.8 ft.

Douglas Co. Surveyors Office - Clell Goodwin - Lenora Ladig - 6/24/1975 - C.S. File 57/30-15

Found - Haines "T" iron & 11" Hemlock bearing N.76°W., 14.1 ft. No sign of SE BT (1960)
A search of the immediate area uncovers no sign of the orig. corner.
New - A 16" Hemlock scribed "T21S R6W S22 CS BT" in a double blaze bears S.43½°W., 26.9 ft.
Note - I do not monument Haines corner but leave "T" iron intact.
Compass decl. 20°