

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 723)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 6" dia., bears S.5°E., 37 lks., mkd: ¼ S BT.
Fir, 9" dia., bears N.68°W., 14 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging Co. - Dec. 1961 - C.S. File 51/222-1

Found - 9" Fir N.68°W., 14 lks.
Set - 1"x1"x36" T. iron.
16" Fir S.53°E., 19.0 ft.

Harvey Christensen - For: Seneca Jones Timber Co. - 1/1999 - M131-17

Found - 1961 1"x1" Haines "T" iron, flush with ground-top broken off
Set - 5/8' X 30' rebar /w YPC "NTCI LS 2603", 0.6 above ground
BTs - 31" D.Fir S.53°E., 19.3 ft., healed face
49" D.Fir N.70.5°W., 8.1 ft., healed face
10' D.Fir N.14.5°E., 28.2 ft., blazed & scribed "¼ S10 BT"
9" D.Fir S.71.5°W., 27,9 ft. blazed & scribed "¼ S15 BT"
Set - 6 ft. Steel post 2 ft., North.