

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 724-5)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked  $\frac{1}{4}$  S on N face; from which  
Cedar, 20" dia., bears N.73°W., 25 lks., mkd:  $\frac{1}{4}$  S BT.  
Cedar, 24" dia., bears S.32°E., 11 lks., mkd:  $\frac{1}{4}$  S BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyors, under Group #1231, surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18059)

-----  
Point for  $\frac{1}{4}$  sec. cor. of secs. 3 & 10, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, with brass cap marked:

T21S R6W  
 $\frac{1}{4}$   $\frac{S \quad 3}{S \quad 10}$   
1985

from which  
A fir, 10" dia., bears S.68 $\frac{3}{4}$ °W., 23 lks., mkd:  $\frac{1}{4}$  S10 BT.  
A fir, 10" dia., bears N.61°W., 6 lks., mkd:  $\frac{1}{4}$  S3 BT.  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.