

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 2 Page(s) 696)

Set post corner to sections 26, 27, 34, & 35; from which

- A Fir, 12" dia., bears N.53°E., 14 lks.
- A Fir, 16" dia., bears S.18°E., 19 lks.
- A Dogwood, 8" dia., bears S.48°W., 5 lks.
- A Fir, 18" dia., bears N.10°W., 15 lks.

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 710)

Cor. to secs. 26, 27, 34 & 35. Renewed the cor. by setting post, 6" dia., 4 ft. long, with marked stone, 12" in ground, T 21 S S 26 on NE, R 6 W S 35 on SE, S 34 on SW, S 27 on NW face, with 2 notches on E & 1 on S edges; from which

- Fir, 12" dia. bears N.53°E., 14 lks. mkd: T21S R6W S26 BT.
- Fir, 16" dia. bears S.18°E., 19 lks. mkd: T21S R6W S35 BT.
- Dogwood, 8" dia., bears S.48°W., 5 lks., mkd: T21S R7W S34 BT.
- Fir, 18" dia. bears N.10°W., 15 lks. mkd: T21S R6W S27 BT.

Wilford N. Haines - For: Harold Woolley - Dec. 1957 - M8-30

Found - Orig. BTs.
 Set - 1"x1"x36" ⊥ rod with brass cap.

BLM Dependent resurvey by Wayne Rogers & Dale Bedell, Cadastral Surveyors, under Group #1392, surveyed Aug./Nov. 1987 - (DCSO records Vol. 48 Page(s) 18468)

The secs. 26, 27, 34, & 35, perpetuated & recorded by Haines in 1958, monumented with an iron rod, 24" long, ½ dia., set 14" in the ground, of which I find no rec. (with a "T" shaped iron rod, 36" long, 1" dia., lying alongside, with a metal washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN ORE) from which the remains of the orig. BTs:

- A root hole, bears S.18°E., 19 lks., with a fir 24" dia., lying alongside, with healed blaze.
- A root hole, bears N.10°W., 15 lks., dist. with a fir 19" lying alongside, with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T21S	R6W
S 27	S 26
S 34	S 35

1987

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new BTs
A fir, 11" dia. bears N.79°E. 15 lks. mkd: T21S R6W S26 BT
A fir, 6" dia., bears S.48½°E., 21 lks., mkd: X BT.
A fir, 10" dia. bears S.41°W. 19 lks. mkd: T21S R7W S34 BT
A fir, 5" dia., bears N.32°W., 13 lks., mkd: X BT.
Deposit the iron rods alongside the stainless steel post.

Fd. BC & accessories by Tony Hostetter 6/2008 - M156-13