

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 710)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which  
Fir, 60" dia., bears N.46°E., 9 lks., mkd: ¼ S BT.  
Fir, 9" dia., bears N.64°W., 19 lks., mkd: ¼ S BT.

-----  
Wilford N. Haines - For: Woolley Logging - Dec. 1961 - M21-74 & M21-75 & C.S. File 51/222-6

-----  
Found - Rock with X  
Stump of 60" Fir N.46°E., 9 lks.  
Set - 1"x1"x36" T iron by rock.  
10" R.Cedar N.15°E., 5.5 ft.  
14" Hemlock N.68°E., 26.5 ft.

-----  
Wilford N. Haines - Sept. 1964 - C.S. File 51/222-2

-----  
This ¼ corner may be destroyed by the construction of logging road so I mark reference point as shown on sketch in C.S. File 51/222.  
Set - 1"x1"x48" to T iron S.67°52'E., 116.36 ft.  
Masonry nail in NW face of Rock outcrop 2'x3' S.67°52'E., 172.68 from orig. corner.

-----  
Donald L Peel, LS #752 - For: IP Co. - July 12, 1982 - C.S. File 58/274 & M92-48

-----  
Found - "T" bar (reference monument) S.67°32'58"E., (1964) 116.36 ft. from I. Pipe.  
Masonry nail in brass disc in rock face, S.67°32'58"E., 56 ft ± from "T" bar.  
Set - 1½"x36" I. pipe w/brass cap in mound of stone mkd: T21S R6W ¼ S27 S 26 PLS 752 1982.  
7" fir, N.89°E., 61.5 ft.  
8" fir, S.8°W., 78.8 ft.

-----  
Tony Hostetter - For: Seneca Jones Tbr Co. - 6/2008 - M156-13

-----  
Found - 1½" iron pipe & brass cap (out of ground) reset at rec. dist. from 2 BTs mkd by Peel in 1982. M92-48  
15" Peel BT, face evident, bears N.87°44'E. 61.50 ft  
16" Peel BT, face evident, bears S.5°40'E., 78.8 ft.  
New BTs- 8" alder, bark scribed "S27 ¼ BT" bears S.35°28'W., 21.8 ft.  
12" Fir scribed "S27 ¼ BT" bears N.9°46'W., 22.9 ft. to spike.