

Alias	Description
Alias	Description
Alias	Description
Alias	Description

DCSO 2½" dia., brass cap on a 1½" O.D. iron pipe, protruding 14" above ground.
An orig. corner stone measures 18"x12"x4" with "X" on flat side, lies loose on top of ground alongside NE side of DCSO BC/IP
DCSO BC/IP bears S.0½°E., 5.0 ft. from Haines T iron (rec. S.4°E., 5 ft.)
Accessories found - (Brgs' & dist. taken from Haines T-iron)
36" now 30" dia., 7 ft. high rotted & burnt D.Fir snag, no scribing visible, bears S.50½°W., 41.8 ft. (orig. rec. S.52°W., 40.9 ft.)
60" now 48" dia., 3 ft. high rotted & burnt D.Fir stump, no scribing visible, bears N.60°W., 66.9 ft. (Orig. rec. N.57°W., 64.0 ft.) Orig. BT
54" now 40" dia., 10 ft. high rotted & burnt D.Fir snag, no scribing visible, bears N.28½°E., 51.3 ft. (orig. rec. N.30°E. 60.7 ft. dist. is a slope measurement) orig. BT.
40" now 38" dia., down, a rotted D.Fir with an open rotted blaze, root hole bears S.42½°E., 67.3 ft. (Orig. rec. S.41°E., 67.3 ft.) Orig. BT.
16" now 30" dia., D.Fir with a fully healed single blaze, bears N.82°W. 17.6 ft. (agrees w/rec) 1960
10" now 15" dia., D.Fir with a fully healed single blaze, bears S.17°E. 10.4 ft. (agrees w/rec) 1960
Set - 1975 DCSO brass cap/iron pipe from 1975 set in error. Brass cap is removed from IP - IP protrudes 11" above ground with a yellow DCSO plastic cap inserted in center.
Orig. stone is placed along NE edge of Haines T iron
From Haines T iron, bearing to orig. BTs have a small rotation to the left. Distances are acceptable. (one slope dist.)
New BT - 13" D.Fir double blazed & scribed "T21S R6W S15 CS BT" bears N.9°W., 25.0 ft.
Note - 1975 DCSO BC/IP set by a proportion method from orig. BTs. Review of distances to BT in field uncover probable distance errors in 1975 ren. resulting in an errant setting of BC/IP.

Harvey Christensen - For: Seneca Jones Timber Co. 1/1999 - M131-17

Found - 1"x 1" Haines "T" iron 1.2 ft. above ground
BTs - 30" D.Fir S.50.5°W., 41.8 ft. 7 ft. snag-no scribing visible.
40 D.Fir N.28.5°E., 51.3 ft. 10 ft. snag-no scribing visible.
continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set -	48" D.Fir, N.60°W., 66.9 ft. 3 ft. stump snag-no scribing visible. 38" D.Fir S.42.5°E. 67.3 ft. blown down. 32" D.Fir N.82°W. 17.6 ft. healed face. 17" D.Fir S.17°E. 10.4 ft. healed face Stone along north east side of "T" iron. 1.5" DCSO pipe /w YPC "DCSO" S.O.5°E) 5.0 FT. 6 ft. steel post 1 ft. North
-------	--