

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor Secs 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 714)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 10, 11, 14, & 15, mkd. T 21 S S 11 on NE, R 6 W S 14 on SE, S 15 on SW, S 10 on NW face, with 4 notches on S & 2 on E edge; from which
 Fir, 40" dia. bears N.45°E., 59 lks. mkd: T21S R6W S11 BT.
 Cedar, 12" dia. bears S.29°E. 32 lks., mkd: T21S R6W S14 BT
 Fir, 40" dia. bears S.84°W., 45 lks. mkd: T21S R6W S15 BT.
 Cedar, 16" dia. bears N.56°W. 9 lks. mkd: T21S R6W S10 BT.

Wilford N. Haines - For: Woolley Logging Co. - 12/1961 - C.S. File 51/222-1

Set - T iron, 1"x1"x36", from old Bearing trees.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - April 1962 - C.S. File 49/143-30

Found - Haines "T" iron & cap at cor. & Cedar snag, now 33", now N.56°W., 5.9 ft. chopped open & fd. good scribing.
 R.Cedar S.29°E., 21.1 ft., now 28" shows good scar. Blaze & rescribe this tree, "T21S R6W S14 CS BT"
 Fir, now 53", N.34°E., (not N.45°E.) 38.9 ft. Old bark sluffing off. No scribing fd., blaze & rescribe (one blaze) "T21SR6WS14CS BT"
 Fir to SW is uprooted & down. Bark all gone, no scribing.

DID NOT SET BRASS CAP

New BTs- 12" Hemlock N.54°W. 42.6 ft. mkd: T21S R6W S10 CS BT
 8" Hemlock S.4°W., 7.2 ft., mkd: T21S R6W S15 CS BT

BLM remonumentation of certain orig. corner points by James E. Jelley, under group #350 surveyed April 1979 - (DCSO records Vol. 43 Page 16479-80)

The cor. of secs. 10, 11, 14, & 15, perpetuated & recorded by Haines in 1961, & further perpetuated & recorded by Godfrey in 1962, monumented with a T shaped iron rod, 1" in cross sec., firmly set projecting 10" above ground, from which the remains of the orig. BTs:

 A root hole, bears N.45°E., 59 lks., with a down fir alongside, 53" dia., no marks visible.

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 32" dia., bears S.29°E., 32 lks., with fragmentary scribe marks visible on open orig. blaze, & healed blaze by Godfrey.

A root hole, bears S.84°W., 45 lks., with a down fir alongside, 50" dia., no marks visible.

A cedar snag, 33" dia., bears N.56°W., 9 lks., with fragmentary scribe marks visible on open blaze.

and BTs mkd. by Godfrey

A hemlock, 10" dia., bears S.4°W., 11 lks., with healed blaze.

A hemlock, 18" dia., bears N.54°W., 63½ lks., with healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T21S R 6W	
S 10	S 11
S 15	S 14
1979	

from which a new BT

A hemlock, 4" dia., bears N.8°E., 34½ lks., mkd: X BT.
Reset T shaped iron rod alongside iron post.

Fd. Ok by R.Ward, June 2002 - M 140-36