

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. Secs. 10 & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 715)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which  
Fir, 40" dia., bears S.75°E., 48 lks., mkd: ¼ S BT.  
Fir, 4" dia., bears N.14°W., 25 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - May 1962 - C.S. File 49/143-2

-----  
Looked for not found.

Robert Ward - For: Seneca Jones Timber Co. - June 2002 - M140-36

-----  
Witness corner to ¼ corner  
Found - Searched for the orig. ¼ corner but did not find it. By proportionate distance - true position of ¼ corner falls within a 16" Fir. I set a WC to the true position for the ¼ corner 12.0 ft. North of said true position.

Set - A 2½" dia., alum. cap on a 5/8"x36" rebar marked:

T21S R6W  
↓ WC ¼  
S10|S11  
12.0 2002  
LS 1091

23" D.Fir bears N.7¾°E., 20.4 ft.  
14" D.Fir bears S.69¾°E., 15.9 ft.  
9" D.Fir bears S.23½°E., 5.6 ft.  
16" D.Fir bears S.1½°E., 11.8 ft.

Note - All new BTs scribed "X BT"