

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 715)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 2, 3, 10, & 11, mkd. T 21 S S 2 on NE, R 6 W S 11 on SE, S 10 on SW, S 3 on NW face, with 5 notches on S & 2 on E edge; from which

Cedar, 10" dia. bears N.20°W., 11 lks. mkd: T21S R6W S3 BT
Hemlock, 10" dia., bears S.65°E., 43 lks., mkd: T21S R6W S11 BT.

Hemlock, 10" dia., bears S.50°W., 26 lks., mkd: T21S R6W S10 BT.

Cedar, 10" dia. bears N.70°E., 48 lks. mkd: T21S R6W S2 BT

Wilford N. Haines - For: Woolley Logging Co. - 12/1961 - C.S. File 51/222-1 (See also DCSO report C.S. 49/143-19 12/1961)

Found - 10" Cedar N.70°E., 48 lks., dead & down.

Hemlock stub S.56°E., 43 lks.

Set - 1"x1"x36" T. iron.

No record of New BTs.

The following note was written alongside the corner renewal in the previous renewal book:

"I state that I saw scribing on this Cedar BT about 1960." signed by Wilford N. Haines. (note added: See FB H-70)

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyors, under Group #1231, surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18058-9)

The cor. of secs. 2, 3, 10, & 11, perpetuated & recorded by Haines in 1961, from orig. evidence no longer in existence, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 6" above ground, with washer mkd:

WILFORD N HAINES

239

SURVEY POINT

DRAIN OR

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, directly over iron rod, with brass cap marked:

T21S R6W
S 3 | S 2
S 10 | S 11
1985

from which

A fir, 9" dia. bears N.40°E., 21½ lks. mkd: T21S R6W S2 BT
continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 9" dia. bears S.85°E. 30½ lks. mkd: T21S R6W S11 BT
A hemlock, 14" dia., bears S.56½°W., 4 lks., mkd: T21S
R6W S10 BT.
A fir, 13" dia. bears N.52°W., 23 lks. mkd: T21S R6W S3 BT
Deposit a white "DEEP-1" magnetic marker at base of
stainless steel post.

Fd. Ok by L. Roberts, 12/1992 - M116-43 & C.S. File 63/149-3I
Fd. Ok by R. Ward, June 2002 - M 140-36