

PRIMARY CORNER DESCRIPTION C.C. for Secs. 2 & 3 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 717)

I set closing cor. to secs. 2 & 3 by driving post, 6" dia., 4 ft. long, with marked stone, 12" in ground mkd. T20S S35 on NE.; T21S S2 CC on SE.; R6W S3 CC on SW. face; with 2 notches on E. and 4 on W. edge; from which

Fir 20" dia., bears N.59°W., 48 lks. dist. mkd. T20S R6W S35 BT.

Fir 24" dia., bears S.60°E., 94 lks. dist. mkd. T21S R6W S2 CC BT.

Alder 8" dia., bears S.40°W., 36 lks. dist. mkd. T21S R6W S3 CC BT.

Douglas Co Surveyors Office - Milo E Godfrey, Deputy - Vernon Tracy; C Putman, crew - Dec. 1961 - C.S. File 49/143-15

Found - Remnant of Fir stump, N.59°W., 31.7 ft., part of old face showing, portion of scribed "B" still intact.

Remnant of old Fir stump, S.60°E., 62.0 ft., no markings found. No trace of SW. BT found.

Set Brass cap at cor. mkd: County Surveyors Office

S 35	T20S R6W
CC S 3 S 2	T21S R6W
	1961

New BTs- 42" Cedar S.72½°W., 152.7 ft. mkd. T21S R6W CC S3 CS BT.

10" D.Fir S.20½°E., 109.7 ft. mkd. T21S R6W CC S2 CS BT.

Haines "T" Iron bears S.66°E., 2.7 ft. Haines BT an 18" Fir bears N.70°E., 106.9 ft., pitched over, scribing not visible. (Possible BT mentioned in Haines F.B. H-75)

Cor. secs. 34 & 35, T20S R6W bears West 238.4 ft. (Rec. 233.6 ft.)

BLM Resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1231, Surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18057-58)

(44.22 chs.)

The original closing cor. of secs. 2 and 3, perpetuated and recorded by Godfrey in 1961, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1961, from which the remains of the original bearing trees:

(Cont. Next Page)

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION C C for Secs. 2 & 3 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A decayed Fir stump size indeterminate, bears S.60°E., 94 lks. dist., no marks visible.

A decayed Fir stump size indeterminate, bears N.59°W., 48 lks. dist., no marks visible.

and bearing trees mkd. by Godfrey:

A Fir 16" dia., bears S.19°E., 167 lks. dist., with healed blaze.

A Cedar 48" dia., bears S.73°W., 230 lks. dist., with healed blaze.

(44.265 chs.)

Intersect the S. bdy. of T20S R6W.

True point for the closing cor. of secs. 2 and 3.

Set an Iron post 30" long, 2" dia., with magnetic, plastic breakaway base, 24" in the ground, with brass cap marked:

T 20 S R 6 W
S 35

S 3 | S 2
C C
T 21 S R 6 W
1984

from which

A Fir 8" dia., bears S.31½°E., 93 lks. dist. mkd. T21S R6W
S2 CC BT.

A Fir 6" dia., bears S.70½°W., 47 lks. dist. mkd. T21S R6W
S3 CC BT.

From this point, a point established by Haines during an unrecorded survey, bears S.30½°E., 0.07 chs. dist., monumented with "T" shaped iron, 1" dia., firmly set, projecting 4" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN OR, from which a bearing tree mkd. by Haines:

A Fir 24" dia., bears N.71°E., 158 lks. dist., with healed blaze.

Fd. OK, Dec. 1992 by L. Roberts - M 116-43 and C.S. 63/149-3A

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2048, surveyed June/July 2003 - (DCSO records Vol. 55 Page(s) 21511-2)

The corner, the original closing cor. of secs. 2 & 3, T21S R6W, bears S.0°26'08"E., 3.05 ft., perpetuated by Godfrey, Deputy County Surveyor, in 1961, monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION C.C. for Secs. 2 & 3 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees
A decayed fir stump, size indeterminate, bears S.61¼°E.,
63.6 ft., no marks visible. (Record, S.60°E., 62.0 ft.)
A decayed fir stump, size indeterminate, bears N.60¼°W.,
39.1 ft., no marks visible. (Record, N.59°W., 31.7 ft.)
and bearing trees mkd. by Godfrey
A fir, 16" dia., bears S.19°E., 110.2 ft., with a healed
blaze.
A double trunk cedar, 64" dia., bears S.73°W., 151.8 ft.
with a healed blaze.
Also from the corner, a point established by Wilford N.
Haines, Oregon Professional Land Surveyor No. 239, in an
unrecorded survey, bears S.31°10'58"E., 4.90 ft., monumented
with an iron "T" post, 1x1", firmly set, projecting 4" above
ground, with aluminum washer mkd.

WILFORD N HAINES
239
SURVEY
POINT
DRAIN ORE

from which a bearing tree mkd. by Haines
A fir, 29" dia., bears N.71°E., 104.3 ft., with a healed
blaze.

Corey Woodruff - For: Woolley Enterprises, Inc. - 4/2013 -
M165-16

Found - Iron pipe w/brass cap per BLM survey.
Douglas Cty. BCIP brs. S.0°39'29"E., 3.02'
Record BLM BTs have fallen & rotted.
New - 13" Maple N.28°E., 26.1'
12" D.Fir N.29°W., 84.3'