

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 537700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T20-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 679)

-----  
Set ¼ sec. post, from which  
An Alder 6" dia., bears S.43°E., 6 lks. dist.  
An Alder 5" dia., bears S.49°W., 50 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - 1961-1962 - C.S. File 49/89-40 - added 7/11/2017

-----  
Corner not found.

BLM Resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1231, Surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18054)

-----  
Point for the ¼ sec. cor. of sec. 35 only, at proportionate distance; there is no remaining evidence of the original corner. Set an Iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 20 S R 6 W
¼ S 35
T 21 S R 6 W
1984

from which  
A Fir 21" dia., bears N.28°E., 45 lks. dist. mkd. ¼ S35 BT  
A Fir 22" dia., bears N.35½°W., 25 lks. dist. mkd. X BT.

Fd. OK, Dec. 1992 by L. Roberts - M 116-43 and C.S. 63/149-3C

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2048, surveyed June/July 2003 - (DCSO records Vol. 55 Page(s) 21510-11)

-----  
The ¼ sec. cor. of sec. 35 only, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.  
from which the bearing trees mkd. by Rogers  
A fir, 26" dia., bears N.26¼°E., 28.8 ft., with a healed blaze. (Record, N.28°E., 29.7 ft.)  
A fir, 24" dia., bears N.39¼°W., 16.5 ft., with a healed blaze. (Record, N.35½°W.)  
Discontinue posting and blazing.

Fd. BC, T-iron & 3 BTs, Corey Woodruff - 4/2013 - M165-16