

TOWNSHIP 21 RANGE 06 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35; & 2, T22-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 692)

Set ¼ sec. post, from which
 An Ash 15" dia., bears N.87°E., 536 lks. dist.
 A B.Oak 30" dia., bears S.20°E., 380 lks. dist.

Wilford N. Haines - For: Harold Woolley - Jan. 21, 1958
M 8-30

Scribed -18" Fir S.45°15'E., 80.1 ft.
 18" W.Oak N.82°30'E., 182.5 ft.
Set 1" x 1" x 36" Iron T-Iron rod with brass cap.

Fd. OK, Aug. 1961, DCSO, C.S. File 49/143-40

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 8/14/2001 - C.S. File 66/21-34

Found - 1958 Haines "T" iron protrudes 12" out of ground.
 Top bent 10" SE.
 18" now 22" dia., 4 ft. high D.Fir stump with fully
 healed blaze, bears S.45¼°E., 80.1 ft. (1958)
 18" now 22" dia., 3 ft. high W.Oak stump with fully
 healed blaze bears N.82½°E., 182.5 ft. (1958)
New - 14" dia., W.Oak double blazed & scribed "¼ S35 CS
 BT" bears N.61°E., 360.6 ft.
 19" dia., W.Oak double blazed & scribed "¼ S2 CS BT"
 bears S.33°W., 157.6 ft.
Compass decl. 17¾°E.
At plumb position of found "T" iron we set a 2 3/8"
dia., brass cap on a 1 3/8" O.D. by 32" long iron
pipe. Protrudes 4" out of ground. "T" iron set
along North edge of BC/IP protrudes 1" out of
ground. MKD: DOUGLAS COUNTY SURVEYOR

T21S
 S 35 R
 S 2 6
T22S W
2001

Set metal witness post and sign 1 ft. East of BC/IP.
Corner is approx. East 300 ft. from old cemetery.